

EAZY CWT-DE

Product Code:	1101	Packaging:	25L
Product Group:	Water Treatment	Issue/Date:	1.50 - 31/07/2015

eazy CWT-DE is an easy to use and effective liquid corrosion inhibitor and treatment for diesel engine cooling water systems, protecting them from corrosion and hard water scale.

Product has no detrimental effects on non-metallic system components such as seals, glands, hoses or gaskets and is compatible with glycol-based antifreeze products.

Application and use

Product is an effective corrosion inhibitor for both ferrous and non-ferrous metals in marine circulating cooling water systems.

Prior to the addition of product sacrificial anodes (e.g. magnesium or zinc) in the cooling system should be removed.

Note: Please contact Eazychem before using this product in systems containing aluminium alloys as product may not be suitable.

Directions for use

Dosage:

Good quality fresh or distilled water should be used to fill the cooling water system. The recommended initial dosage is 10 litres per tonne of system capacity.

The initial treatment should be dosed into a suitable point in the cooling system and circulated for one hour to ensure even distribution. For advice contact Eazychem.

Testing & Control:

The correct concentration of product treatment should be maintained using Eazychem cooling water test kits.

Testing should be carried out once per week to ensure that a minimum level of nitrite is maintained. This should be 900 to 1400ppm as nitrite (NO₂) and logged onto the control and dosage chart.

Health and Safety

Please refer to the Material Safety Data Sheet and Product Label for specific information.

Limitation of Liability

Eazychem's standard **terms and conditions** of sale, available on request, apply and contain limitations on any liability that may be incurred by Eazychem arising in any way from the sale and use of products supplied by Eazychem.